



BLPAR12 & BLPAR4 - **BATTERY LIGHT**
Horeca Light Technology



BLPAR12 & BLPAR4 BL series

PAR12 Battery Light



PAR4 Battery Light



PAR12 & PAR4 Battery Light series

ORDER CODE: UNIBLPAR12

ORDER CODE: UNIBLPAR4

	PAR12	PAR4
Power input	100-240VAC 50/60Hz	100-240VAC 50/60Hz
Power Consumption	100W max	45W max
Power Connectors	IEC input/output	Built-in charging base
Data Connectors	3-pin DMX In/Out connections, IP rated 20 cm In/Out pigtails with waterproof DMX data connector	3-pin DMX In/Out connections, IP rated 20 cm In/Out pigtails with waterproof DMX data connector
Battery type	Rechargeable lithium-ion battery with LG chem	Rechargeable lithium-ion battery with LG chem
Recharging time	Around 6 hours	Around 6 hours
Battery life	6 hours FC from one charge Around 12 hours at running preset programs Around 18 hours at running any single color	6 hours FC from one charge Around 12 hours at running preset programs Around 18 hours at running any single color
Led	12 x 10W RGBW 4-in-1	4 x 12W RGBWA+UV hex color
Beam angle	25°	30°
Filed angle	50°	58°
Led average life span	Over 50.000 hours	Over 50.000 hours
Dimming	0-100% dimming	0-100% dimming
Strobe	0-25Hz	0-25Hz
Preset program	25 preset programs	30 preset programs
Control mode	DMX512, Master/Slave, Auto Run, Wireless DMX, Infrared remote control	DMX512, Master/Slave, Auto Run, Wireless DMX, Infrared remote control
Control panel	4 digit led display	4 digit led display
DMX channel	4/6/11 channels	6/8/12 channels
Housing	Rigid aluminum housing	Rigid aluminum housing
Rigging	Double bracket for rigging on truss or sitting on floor	Double bracket for rigging on truss or sitting on floor
Housing color	Black	Black
Net weight	8.0 Kg	4.6 Kg
Working temperature	-10° ~ +40° C	-10° ~ +40° C
IP rating	IP65	IP65